

EMLID

REACH RS2

Datasheet



Key features

- Tracks GPS/QZSS L1C/A, L2C GLONASS L1OF, L2OF BeiDou B1I, B2I Galileo E1-B/C, E5b SBAS L1C/A
- Fast RTK convergence
- Multi-feed antenna with multipath rejection
- 868/915 MHz LoRa modem for up to 8 km connectivity
- Global 3.5G modem
- 22 hours on 1 charge
- NTRIP and VRS support, works with RTCM3
- Logs RINEX at update rate up to 20 Hz
- 16 GB of internal storage
- IP67, water- and dustproof

REACH RS2

Technical specifications

POSITIONING

Precision	Static	H: 4 mm+0.5 ppm
	PPK	H: 5 mm+0.5 ppm
	RTK	H: 7 mm+1 ppm
Convergence time		~5 s typically
Signal tracked		GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b, SBAS, L1C/A
Number of channels		184
Update rates		20 Hz GPS / 5 Hz GNSS
IMU		9DOF

CONNECTIVITY

UHF LoRa radio	Frequency range	868/915 MHz
	Power	0.1 W
	Distance	Up to 8 km
3.5G modem	Regions	Global
	Bands	Quad-band, 850/1900, 900/1800 MHz
	SIM card	Nano-SIM
Wi-Fi		802.11a/b/g/n
Bluetooth		4.0/2.1 EDR
Ports		RS-232, USB Type-C
Data Protocols		NTRIP, VRS, RTCM3, position output in NMEA, LLH/XYZ
Data logging		RINEX at update rate up to 20 Hz
Internal storage		16 GB

MECHANICAL

Dimensions	126x126x142 mm
Weight	950 g
Temperature	-20...+65 °C
Ingress protection	IP67 water- and dustproof

ELECTRICAL

Autonomy	16 hrs as 3.5G RTK rover, 22 hrs logging
Battery	LiFePO4 6400 mAh, 6.4 V
External power input	6–40 V
Charging	USB-C 5 V 2 A

COMMUNICATIONS AND DATA STORAGE

- 9PIN port: RS-232, PPS, Event
- USB OTG
- **Internal Radio**
Modem: LoRa technology
Reliable link on up to 8 km baseline
Transmit power up to 100 mW
Configurable 862–1020 MHz carrier
- **Internal 3.5G modem**
Global
Quad-band, 850/1900, 900/1800 MHz
- Built-in short-range Wi-Fi 802.11a/b/g/n, WEP, WPA, WPA2 encryption
- Built-in short-range Bluetooth 4.0/2.1 EDR
- Data storage 16 GB internal memory
- Raw logs in RINEX, UBX
- External Radio Modem connectivity over RS-232/USB OTG
- RTCM 3.x input and output over Wi-Fi, Bluetooth, LoRa, USB, RS-232, NTRIP
- NMEA 0183, ERB output over Wi-Fi, Bluetooth, USB, RS-232
- ReachView app for iOS and Android for configuration and surveying



YOUR LOCAL DEALER

FRANCE

DRONES IMAGING
TRAINING, ANALYSIS & AERIAL IMAGERY PROCESSING

www.dronesimaging.com